Field Testing of Multiple Simultaneous Vibrators Controlled by Filtered m-Sequences

Joe Wong, CREWES and David Langton, Devon Energy Corp.






Introduction


Motivation:


Increased efficiency in completing highresolution 3D land surveys.


Method:


Use multiple simultaneous vibrators sources controlled by quasi- orthogonal pilot signals.









































































































































































































































































































































































QUASI-ORTHOGONAL SET OF FOUR PURE M-SEQUENCES





Wong, J., 2012. Multiple simultaneous vibrators controlled by m-sequences: CREWES Research Report, 24, 86.1-86-20.

Two Simultaneous Vibrators








Pure m-Sequences

Time, ms


Filtered m-Sequences









Blended raw field data for two simultaneous vibrators. Filtered m-sequence pilots = mSeq-1F and mSeq-2F. Sweep Time ~ 16.4 s, Listen Time ~ 22 s.




CSG for V1 source, deblended/extracted with mSeq-1F pilot.





CSG for V2 source, deblended/extracted with mSeq-2F pilot.









































Conclusion

- Filtered m-sequence pilots and linear sweep pilots are equally suitable for controlling land vibrators.
- In numerical simulations, improved filtered m-sequence pilots (with carefully controlled spectra) are effective in deblending very weak signals from very strong signals.
- We will continue to field-test simultaneous multisourcing using the improved filtered m-sequence pilots to control four and eight vibrators.

ACKNOWLEDGEMENTS

We thank:

- Keith Radcliffe and Tom Phillips for assisting with setting up custom pilot signals in the vibrator controllers;
- Devon Energy Corporation for permission to present these results.

CREWES is supported by its industrial sponsors and by the Natural Sciences and Engineering Research Council of Canada (NSERC).

INVITATION TO COLLABORATE

- Field-test simultaneous multi-sourcing.
- Use 1, 2, 4 or 8 vibrators.
- Control with improved m-sequence pilots.

Contact me: wongjoe@ucalgary.ca