

# Direct measurement of frequency-dependent phase velocities from Snowflake data

Chioma Chineke and Kris Innanen

chioma.chineke1@ucalgary.ca

## Summary

- Analyzing the VSP datasets from the Newell County facility enhances the understanding of seismic data in the near-surface.
- Phase velocity estimates changes with the direction of wave propagation.
- Estimating the frequency-dependent phase velocities in the near-surface is integral to determining the Q-factor of seismic waves.
- These phase velocity estimates could be used as initial model for frequency-dependent velocity model.

## Results




FIG 4: Gabor spectrum of a seismic trace




FIG 5: Picking of the arrival and departure times of the frequencies





FIG 8: Calculation of Tcal from the group velocity of the P-wave.

## Method

$$V_p(f) = \frac{L}{\Delta T(f)}$$

$$L = \sqrt{x^2 + z^2}$$

$$\Delta T(f) = T_M(f) - T_s(f)$$




FIG 1: Schematic diagram of the source and receivers locations.




FIG 2: Uncorrelated seismic traces




FIG 3: Source signal





FIG 6: Travel time of the frequencies

$$V_p(f) = \frac{L}{T_M(f) - T_s(f) - T_{cal}}$$





FIG 7: Calibration of the raw phase velocities




FIG 9: Phase velocity maps at different frequencies along Line 1




FIG 10: Phase velocity maps at different frequencies along Line 5




FIG 11: Phase velocity maps at different frequencies along Line 10




FIG 12: Phase velocity maps at different frequencies along Line 12

## Acknowledgements

The sponsors of CREWES are greatly thanked for their continued support. This work was funded by CREWES sponsors, NSERC(Natural Science and Engineering Research Council of Canada), through the grant CRDPJ 543578-19. This work was done in collaboration with the Carbon Management Canada. Likewise, thank you Joe Wong for your huge assistance and for allowing me to use your MER code for picking arrival times. Thank you Tianze for your assistance.

## References

- Aki, K., and Richards, P. G., 2002, Quantitative Seismology: University Science Books, 2nd edition.  
 Kris Innanen, 2014, Estimating anelastic dispersion from uncorrelated vibs data, vol 16: CREWES Reports  
 Macquet, M., Lawton, D. C., Saeedfar, A. A., and Osadetz, K. G., 2019, A feasibility study for detection thresholds of CO<sub>2</sub> at shallow depths at the CaMI Field Research Station, Newell County, Alberta, Canada: *Petroleum Geoscience*, 25, no. 4., 509-518.  
 Margrave, G. F. and Lamoureux, M. P., 2002, Gabor deconvolution: CREWES Annual Research Report, 13.  
 McDonal F. J., F. A. Angona, R. L. Mills, R. L. Sengbush, R. G. Van Nostrand, and J. E. White, 1958, Attenuation of shear and compressional waves in Pierre shale: *Geophysics*, 23, 421-439.  
 Sun LF, Milkereit B, Tisato N. Analysis of velocity dispersion using full-waveform multichannel sonic logging data: A case study. *Geophysical Prospecting*. 2016 Jun 28;64(4):1016-29.  
 Wong, J., Han, L., and Bancroft, J.C., 2009. Time picking and random noise reduction on microseismic data: CREWES Report, vol. 21.